

雙GPRS雙模雙頻雙向雙通

雙模雙頻 雙向雙通 雙模雙頻 雙向雙通 雙模雙頻 雙向雙通 Omni雙模雙頻 雙向雙通

雙模雙頻 雙向雙通 雙模雙頻 雙向雙通 雙模雙頻 雙向雙通



— ABOUT THE LOCK —



APP control



Remote control



Ultrasonic sensing



Geomagnetic sensing

— APPEARANCE —



THE NEW
DESIGN,
MORE INTELLIGENT



NEW MATERIAL,
SECURITY AND
SMART



— OVER LOOKING —



FEATURES

Overvoltage Protection

- ◆ 180°Crashproof
- ◆ Automatic reset
- ◆ Anti-dismantle



Waterproof &
Anti-corrosion

IP67





Battery box waterproofing work



Battery	D size battery*4	Height - after up	360mm
Quiescent current	$\leq 1.5\text{mA}$	Operating current	$\leq 1\text{A}$



LOCK CYLINDER Vandal-proof fitting

Operating ambient temperature

-10°C ~ 60°C

Net Weight

4.95KG



2G Network

Run time-up, down

≤5S



65MM



380MM



360MM





OPERATION

SHARING
MODE

APP unlock
Sensor lock
Automatic charge

The cars pass through the barrier gate automatically after the APP connect with the cloud; the parking lock opens automatically when the car comes near and it closed when the car leaves.

Product Features

- Custom Question**

Omni



Flow chart



Workshop



Exhibition



Package



R&D Team



Sale Team



Business Negotiations



Shipping